







FIND THE RIGHT PRODUCT FOR YOUR VENTING NEEDS

Ducts and Hook Up Kits



APPLICATION						
	SOLUTIONS					
UL2158 A listed	✓	✓		✓		
Tight Space Dryer Hook Up					✓	
Max Operating Temp 435°F	✓	✓	✓		✓	
Max Operating Temp 250°F				✓		✓
Offers Maximum Flexibility				✓		✓
Max durability for robust install	✓	✓				
Available Sizing	4"	4"	3" - 8"	4"	4"	3" - 20"



CLOTHES DRYER



BATHROOM FAN



KITCHEN RANGE HOOD



For more information about these products, visit our website at www.dundasjafine.com

TROUVEZ LE PRODUIT ADAPTÉ À VOS BESOINS DE VENTILATION

Conduits et trousses de raccordement

TROSSE
ENTIÈREMENT EN
MÉTAL ULTRA-
ROBUSTE



CONDUIT UL
SEMI-RIGIDE



CONDUIT SEMI-
RIGIDE STANDARD



ProFlex
CONDUIT UL
EN FEUILLE
D'ALUMINIUM









CONDUIT
ÉCONOMISEUR
D'ESPACE



CONDUIT À
USAGE GÉNÉRAL
EN ALUMINIUM



UTILISATION						
	SOLUTIONS					
Homologué UL2158 A	✓	✓		✓		
Raccordement de sècheuse à espace restreint					✓	
Température de fonctionnement maximale 435 °F	✓	✓	✓		✓	
Température de fonctionnement maximale 250°F				✓		✓
Offre une flexibilité maximale				✓		✓
Durabilité maximale pour une installation robuste	✓	✓				
Dimensionnement disponible	4"	4"	3" - 8"	4"	4"	3" - 20"



SÈCHEUSE À
VÊTEMENTS



VENTILATEUR DE
SALLE DE BAIN



HOTTE DE
CUISINE



Pour plus d'informations sur ces produits, visitez notre site Web à l'adresse www.dundasjafine.com